

**UNITED STATES PATENT APPLICATION**  
**FOR**  
**ENDOSCOPIC STENT DELIVERY SYSTEM AND METHOD**

**BY**  
**JAMES F. HEMERICK**  
**AND**  
**ERIC SCHNEIDER**

LAW OFFICES

FINNEGAN, HENDERSON,  
FARABOW, GARRETT,  
& DUNNER, L.L.P.  
1300 I STREET, N. W.  
WASHINGTON, DC 20005  
202-408-4000

## DESCRIPTION OF THE INVENTION

### Field of the Invention

[001] The present invention relates to stent delivery systems and methods. More particularly, the present invention relates to endoscopic stent delivery systems and methods.

### Background of the Invention

[002] Medical stents may be used in a variety of medical procedures. Such stents may be used to provide structural support to an anatomical structure, such as a fluid vessel, in order to prevent the structure from collapse, widen the lumens of such structures to reverse an occluded state, or allow other material to be injected or removed through the anatomical structure. Typically, such medical stents are delivered to a target anatomical structure in a tissue system via stent delivery systems. These stent delivery systems may be elongated devices that are through fluid vessels into or in proximity to target organs or tissue systems. Once in position, an outer tubular projection of the stent delivery system is retracted proximally while an inner portion, which maintains a stent in its distal end, is stationed in place. This relative movement of the outer tubular portion with respect to a stationary inner portion serves to deploy and position the stent in place. Use of such medical stents has allowed medical personnel to perform procedures that widen fluid vessels in a relatively rapid and non-invasive manner.

LAW OFFICES

FINNEGAN, HENDERSON,  
FARABOW, GARRETT,  
& DUNNER, L.L.P.  
1300 I STREET, N. W.  
WASHINGTON, DC 20005  
202-408-4000



55D, may result in stretching or breakage after application of a high force, but typically allows better tracking through tortuous anatomy because of the added flexibility.

[004] Thus, it would be advantageous for a stent delivery system to have sufficient strength and stiffness to minimize kinking, stretching, and breakage, while at the same time, be flexible enough to be easily led through tortuous anatomy in the body.

### **SUMMARY OF THE INVENTION**

[005] The advantages and purpose of the invention will be set forth in part in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The advantages and purpose of the invention will be realized and attained by means of the elements and combinations particularly pointed out in the appended claims.

[006] To attain the advantages and in accordance with the purpose of the invention, as embodied and broadly described herein, an exemplary embodiment of the invention includes a system for delivering a stent into an anatomical structure. The system comprises an outer tubular structure having a proximal end and a distal end and an inner elongated structure. The inner elongated structure comprises a proximal end and a distal end and is located within the outer tubular structure such that the distal end of the inner elongated structure substantially coincides with the distal end of the outer tubular structure. The inner elongated structure has a stent accommodating area on its distal end, and an external tubular structure contact area projecting from its surface and

LAW OFFICES

FINNEGAN, HENDERSON,  
FARABOW, GARRETT,  
& DUNNER, L.L.P.  
1300 I STREET, N. W.  
WASHINGTON, DC 20005  
202-408-4000

located proximal to the stent accommodating area. The external tubular structure contact area frictionally slides against an interior surface of the outer tubular structure.

[007] In another exemplary embodiment, there is a gap between an external surface of the inner elongated structure and the interior surface of the outer tubular structure.

[008] In another exemplary embodiment, the external tubular contact area on the inner elongated structure is constructed of Pellethane.

[009] In yet another exemplary embodiment, there are a plurality of external tubular structure contact areas, wherein each subsequent proximal external tubular structure contact area on the surface of the inner elongated structure increases in durometer from the distal end to the proximal end of the inner elongated structure.

[010] In another exemplary embodiment, the invention includes an inner elongated structure for a tubular stent delivery device used in deploying a stent into an anatomical structure. The inner elongated structure comprises an elongated structure, a stent accommodating area on a distal end of the elongated structure and shaped to receive a constrained length of a stent, and an engagement area projecting from the surface of the elongated structure and located proximal to the stent accommodating area. The engagement area is able to frictionally slide against an interior surface of an outer tubular structure of a stent delivery device.

[011] In a further exemplary embodiment, the invention includes an inner elongated structure for a tubular stent delivery device used in deploying a stent into an anatomical structure. The inner elongated structure comprises an elongated structure, stent accommodating means for accommodating a constrained length of a stent at a

LAW OFFICES

FINNEGAN, HENDERSON,  
FARABOW, GARRETT,  
& DUNNER, L.L.P.  
1300 I STREET, N. W.  
WASHINGTON, DC 20005  
202-408-4000

distal end of the elongated structure, and engagement means for frictionally engaging the elongated structure with an interior surface of an outer tubular structure of a stent delivery device.

[012] In another exemplary embodiment, the invention includes a method of deploying a stent with respect to an anatomical structure. The method includes providing a stent delivery system, wherein the system comprises an outer tubular structure having a proximal end and a distal end, an inner elongated structure having a proximal end and a distal end and is located within the outer tubular structure such that the distal end of the inner elongated structure substantially coincides with the distal end of the outer tubular structure. A stent accommodating area on the distal end of the inner elongated structure accommodates a stent. An external tubular structure contact area projecting from a surface of the inner elongated structure and located proximal to the stent accommodating area slides against an interior surface of the outer tubular structure. The method includes inserting the stent delivery system through an insertion point in a body until the distal ends of the external tubular structure and the inner elongated structure are in a position within the anatomical structure, and moving the outer tubular structure proximally while maintaining the position of the inner elongated structure, thus exposing the stent accommodating area and releasing at least part of the stent into the anatomical structure, and continuing the proximal movement of the outer tubular structure with respect to the inner elongated structure until the stent is completely deployed into the anatomical structure, and withdrawing the stent delivery system from the insertion point in the body.

LAW OFFICES

FINNEGAN, HENDERSON,  
FARABOW, GARRETT,  
& DUNNER, L.L.P.  
1300 I STREET, N. W.  
WASHINGTON, DC 20005  
202-408-4000

[illegible][illegible]

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
1	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
2	2	1	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
3	3	2	1	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
4	4	3	2	1	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
5	5	4	3	2	1	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81																			

[illegible][illegible][illegible][illegible][illegible]

[illegible]

Variable	Mean	SD	Min	Max
Age	35.2	10.5	22	55
Gender	50% Male			
Marital Status	65% Married			
Education	12.5 years	2.5	9	16
Income	\$35,000	\$15,000	\$10,000	\$70,000
Health Status	75% Good			
Stress Level	4.5	1.5	1	7
Life Satisfaction	5.5	1.5	1	7
Work-Life Balance	4.0	1.5	1	7
Family Support	6.0	1.5	1	7
Community Involvement	3.5	1.5	1	7
Personal Growth	4.5	1.5	1	7
Relationship Quality	5.5	1.5	1	7
Overall Well-being	5.0	1.5	1	7

Variable	Mean	SD	Min	Max
Age	35.2	10.5	22	55
Gender	50% Male			
Marital Status	65% Married			
Education	12.5 years	2.5	9	16
Income	\$35,000	\$15,000	\$10,000	\$70,000
Health Status	75% Good			
Stress Level	4.5	1.5	1	7
Life Satisfaction	5.5	1.5	1	7
Work-Life Balance	4.0	1.5	1	7
Family Support	6.0	1.5	1	7
Community Involvement	3.5	1.5	1	7
Personal Growth	4.5	1.5	1	7
Relationship Quality	5.5	1.5	1	7
Overall Well-being	5.0	1.5	1	7

Variable	Mean	SD	Min	Max
Age	35.2	10.5	22	55
Gender	50% Male			
Marital Status	65% Married			
Education	12.5 years	2.5	9	16
Income	\$35,000	\$15,000	\$10,000	\$70,000
Health Status	75% Good			
Stress Level	4.5	1.5	1	7
Life Satisfaction	5.5	1.5	1	7
Work-Life Balance	4.0	1.5	1	7
Family Support	6.0	1.5	1	7
Community Involvement	3.5	1.5	1	7
Personal Growth	4.5	1.5	1	7
Relationship Quality	5.5	1.5	1	7
Overall Well-being	5.0	1.5	1	7

Variable	Mean	SD	Min	Max
Age	35.2	10.5	22	55
Gender	50% Male			
Marital Status	65% Married			
Education	12.5 years	2.5	9	16
Income	\$35,000	\$15,000	\$10,000	\$70,000
Health Status	75% Good			
Stress Level	4.5	1.5	1	7
Life Satisfaction	5.5	1.5	1	7
Work-Life Balance	4.0	1.5	1	7
Family Support	6.0	1.5	1	7
Community Involvement	3.5	1.5	1	7
Personal Growth	4.5	1.5	1	7
Relationship Quality	5.5	1.5	1	7
Overall Well-being	5.0	1.5	1	7

Variable	Mean	SD	Min	Max
Age	35.2	10.5	22	55
Gender	50% Male			
Marital Status	65% Married			
Education	12.5 years	2.5	9	16
Income	\$35,000	\$15,000	\$10,000	\$70,000
Health Status	75% Good			
Stress Level	4.5	1.5	1	7
Life Satisfaction	5.5	1.5	1	7
Work-Life Balance	4.0	1.5	1	7
Family Support	6.0	1.5	1	7
Community Involvement	3.5	1.5	1	7
Personal Growth	4.5	1.5	1	7
Relationship Quality	5.5	1.5	1	7
Overall Well-being	5.0	1.5	1	7

Variable	Mean	SD	Min	Max
Age	35.2	10.5	22	55
Gender	50% Male			
Marital Status	65% Married			
Education	12.5 years	2.5	9	16
Income	\$35,000	\$15,000	\$10,000	\$70,000
Health Status	75% Good			
Stress Level	4.5	1.5	1	7
Life Satisfaction	5.5	1.5	1	7
Work-Life Balance	4.0	1.5	1	7
Family Support	6.0	1.5	1	7
Community Involvement	3.5	1.5	1	7
Personal Growth	4.5	1.5	1	7
Relationship Quality	5.5	1.5	1	7
Overall Well-being	5.0	1.5	1	7

Variable	Mean	SD	Min	Max
Age	35.2	10.5	22	55
Gender	50% Male			
Marital Status	65% Married			
Education	12.5 years	2.5	9	16
Income	\$35,000	\$15,000	\$10,000	\$70,000
Health Status	75% Good			
Stress Level	4.5	1.5	1	7
Life Satisfaction	5.5	1.5	1	7
Work-Life Balance	4.0	1.5	1	7
Family Support	6.0	1.5	1	7
Community Involvement	3.5	1.5	1	7
Personal Growth	4.5	1.5	1	7
Relationship Quality	5.5	1.5	1	7
Overall Well-being	5.0	1.5	1	7



[028] Fig. 6b is a planar cross-section along line A-A of the exemplary embodiment of an inner assembly of the stent delivery system of this invention depicted in Fig. 6a.

[029] Fig. 6c is a longitudinal cross-section along line B-B of the exemplary embodiment of an inner assembly of the stent delivery system of this invention depicted in Fig. 6b.

### **DESCRIPTION OF THE PREFERRED EMBODIMENTS**

Reference will now be made in detail to the exemplary embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

[030] The present invention includes a stent delivery system and method that allows for easy stent delivery system manipulation through a human body while maintaining structural stability. Furthermore, a stent delivery system according to embodiments of this invention resists kinking and breakage by being constructed of material and in such a configuration that resists structural compromise while being led through tortuous body anatomy. The stent delivery system according to embodiments of this invention also inhibits friction by minimizing the contact area between the inner and outer assemblies, when one assembly is moving with respect to the other one of the stent delivery device, by allowing a clearance space to exist between the two assemblies. Furthermore, use of particularly resilient material on the inner assembly promotes flexibility while maintaining structural stability. In another exemplary embodiment of the invention, the inner assembly includes use of increasingly flexible

Attorney's Office

LAW OFFICES

FINNEGAN, HENDERSON,  
FARABOW, GARRETT,  
& DUNNER, L.L.P.  
1300 I STREET, N. W.  
WASHINGTON, DC 20005  
202-406-4000

material from the inner assembly's proximal to distal end, thus achieving greater flexibility of the stent delivery device where the flexibility may be needed more to wind through tortuous anatomy, closer to the distal end.

[031] One illustrative embodiment of the invention shown in Figs. 1-5 is a stent delivery system 100, as shown in operation in Figs. 1 and 2a-2c. First, a method of operation of the system 100 will be described with reference to Figs. 1 and 2a-2c to facilitate the later discussion of the structural features of the system 100.

[032] The stent delivery system 100 may be divided into a generally tubular delivery assembly 101 and a stent 102. The delivery assembly 101 typically has multi-concentric elongated tube assemblies, which may include at least an outer tube assembly 105, that extends a substantial length of the delivery assembly 101. The delivery assembly 101 may also include an inner elongated structure 104, that may be a tubular assembly, by example, that typically extends the entire length of the delivery assembly 101, and also communicates with a stent 102 that is in contact with its distal end. The stent 102 may be a braided metallic, polymeric, or other suitable stent that typically is maintained in a stressed, compressed, and elongated state within the outer assembly 105 and is movable by the inner assembly 104. The stent 102, once placed in position into an anatomical structure 191, in a process called deployment, may act as a structural framework in maintaining the geometry of the anatomical structure 191. This interaction of the stent 102 with the outer tube and inner tube assemblies, 105 and 104, respectively, will be discussed in more detail below. Furthermore, the relative terms, proximal and distal, as used herein and throughout the specification, will be given

LAW OFFICES

FINNEGAN, HENDERSON,  
FARABOW, GARRETT,  
& DUNNER, L.L.P.  
1300 I STREET, N. W.  
WASHINGTON, DC 20005  
202-408-4000

its conventional medical definition in that proximal means relatively further away from the body and distal means relatively further into the body.

[033] As shown in Fig. 1, the tubular delivery assembly 101 may be introduced into a patient's body 190 through an insertion point 192, which may be a natural orifice, such as the esophagus, for example, or a suitable invasive insertion point, such as through a suitable incision in the skin, as deemed by a health care worker. Most endoscopic devices are inserted through an endoscope. After introducing the delivery assembly 101 into the patient 190 through insertion point 192, the health care worker would direct the delivery assembly 101 through the natural internal anatomy of the patient until the distal end of the delivery assembly reaches a pre-determined target area, such as the anatomical structure 191. An anatomical structure 191 may include blood vessels, such as the aorta or coronary blood vessels, enzyme vessels, such as the bile duct, colonic structures and the like, or other suitable anatomical structure that may need to have a stent 102 positioned within for appropriate medical reasons.

[034] As shown in Fig. 2a, when the stent delivery assembly 101 has been positioned into a pre-determined suitable position in the body 190, with its distal end 103a located within or in desired proximity to a target anatomical structure 191, deployment of the stent 102 may be initiated. The delivery assembly 101 typically has an inner assembly 104 and an outer assembly 105. The inner assembly 104 is usually longer than the outer assembly 105, but not necessarily. The inner assembly 104 may be an elongated structure, such as a tube with an interior that opens at both its distal end 104d and its proximal end 104p to allow for guidewire access or communication of fluids through the inner assembly 104. Such fluids that may be communicated through

FOIA b 7 - D

LAW OFFICES

FINNEGAN, HENDERSON,  
FARABOW, GARRETT,  
& DUNNER, L.L.P.  
1300 I STREET, N. W.  
WASHINGTON, DC 20005  
202-408-4000

the inner assembly may include enzymes that may destroy structures, such as physiological stones, that block the passages of fluid vessels. Furthermore, an injection port 106, controllable by a shut-off valve 107, may allow for desired fluids to be introduced into the narrow gap space 108 between exterior surface of the interior assembly 104 and the interior surface of the outer assembly 105. Fluids that may be introduced through injection port 106 may include lubricating fluids to promote relative movement of the inner and outer assemblies with respect to each other. Additional structures that may be included on the stent delivery system 100 include a handling structure 116 to allow a health care worker to easily move the inner 104 and outer 105 assemblies with respect to each other, and a lead point 117, typically conical, that eases the directional movement of the delivery assembly 101 through body anatomy.

[035] Deployment of the stent 102, as shown in Fig. 2b, may be initiated by holding steady the inner assembly 104 while moving the outer assembly 105 proximally in the direction of the arrow 110. This relative proximal movement of the outer assembly 105 with respect to the inner assembly 104 exposes the stent 102 housed near the distal end 103a of the outer assembly 105. The released stent 102 then may promote the structural integrity of the anatomical structure 191. Because the stent 102 may be in a compressed and elongated state within the outer assembly 105, sufficient force must be imposed on the outer assembly 105 to initiate movement with respect to the inner assembly 104. Such a force must overcome the countering frictional forces caused by the relative movement of any contacting area between the outer surface of the inner assembly 104 and the interior surface of the outer assembly 105, the radial frictional force imposed by the constrained stent on the interior surface of the outer

LAW OFFICES

FINNEGAN, HENDERSON,  
FARABOW, GARRETT,  
& DUNNER, L.L.P.  
1300 I STREET, N. W.  
WASHINGTON, DC 20005  
202-406-4000







jacket 104a may provide interior support to the distal exterior tube region 105a. As shown in Figs. 4a-4c, the layer of Pellethane typically is on a shortened jacket 104a of a conventional material, such as PEEK, used as a material for the inner elongated structure 104b, which will be described as a tube in the illustrated embodiments. This jacket 104a is of sufficient length to support the non-braided, clear portion of the exterior tube 105a during, for example, reconstraint around a curve. The jacket 104a typically is longer than the longest constrained length of the stent 102 to provide support for the stent 102. The combination of the inner assembly 104, having a jacket 104a with a layer of pellethane thereon, with the outer assembly 105, results in an endoscopic delivery system with excellent force transmission, a flexible stent region, and low requisite deployment/restraint forces in tortuous anatomies.

[041] To further inhibit friction and promote ease in operation of the stent delivery system 100, a gap 108 may be created between the outer surface of the inner assembly 104 and the inner surface of the outer assembly 105. This gap 108 may be approximately 0.005", but may range from 0.004 to 0.008". The gap 108 may be increased as the diameter of the tubes creating its walls are increased. Furthermore, there may be a short length in neckdown to fit into the stainless steel counterbore to support the proximal region. Such support of the proximal region is similar to a flexible transition.

[042] The distal jacket 104a may be thermally attached proximal to the distal portion of the interior tube 104b. This jacket 104a may be a length that would support a constrained length of the stent 102, which typically is longer than its unconstrained length. A typical length for the jacket 104a may be approximately 130 mm. However,

LAW OFFICES

FINNEGAN, HENDERSON,  
FARABOW, GARRETT,  
& DUNNER, L.L.P.  
1300 I STREET, N. W.  
WASHINGTON, DC 20005  
202-408-4000



the length of the jacket 104a may be changed to accommodate stents 102 of different lengths. More particularly, the length of the jacket 104a may be that of the longest constrained stent length in order to provide internal support to the exterior tube assembly 105 until the point where the stent 102 is fully deployed into the anatomical structure 191. The proximal end of the stent 102 may be in communication with a holding cup 133 that holds the proximal end of the stent 102 and a holding sleeve 104c that is attached near the distal end of the inner assembly 104. The holding sleeve 104c may be an opaque sheet of plastic, such as Tecothane, for example, in a distinct color, such as red, for example, that holds the proximal end of the stent 102 and also serves as a visual indicator to a health care worker of the proximal end of the stent 102. The holding sleeve 104c may accommodate the stent 102 by friction, such as by laser cutting polymer from wire to create bare stent ends, and leaving silicone ribs on the backside of the wire, thus providing a high friction surface that comes in contact with the holding sleeve 104c. Additionally, during deployment, visual signal bands 131 that may be adjacent the holding sleeve 104c, and which may be radiopaque such as, for example, tantalum or platinum, may become visible through a fluoroscope through the clear portion of the exterior tube 105a, such that a health care worker would be signaled that the stent 102 is close to being deployed, thus if reconstraint is necessary to reposition the stent 102, it would be time to do so. The stent 102 is free to move independently of the outer assembly 105 as directed by the inner assembly 104. As discussed above, to activate deployment of the stent 102, the outer assembly 105 typically is retracted proximally which moves the non-braided region 105a over the inner member jacket 104a. During reconstraint of the stent 102, the inner assembly 104

LAW OFFICES

FINNEGAN, HENDERSON,  
FARABOW, GARRETT,  
& DUNNER, L.L.P.  
1300 I STREET, N. W.  
WASHINGTON, DC 20005  
202-408-4000

may be pulled proximally while the exterior assembly 105 remains stationary. The low friction response of the jacket 104a with the interior lining of the outer assembly 105 typically results in less resistance than conventional stent deployment assemblies because there is a limited area of contact between the two assemblies. In an exemplary embodiment, Pellethane tubing is used as the jacket 104a material and PTFE is used as the interior surface lining of the exterior assembly 105. Alternatively or additionally, the surface of the jacket 104a may be lubricated with a suitable lubricant such as MDX silicone to further decrease frictional forces opposing relative movement between the two assemblies. Other materials, besides Pellethane, also may be used for the jacket 104a as long as the materials exhibit relatively low frictional forces when in contact with the interior surface of the outer assembly 105. Such alternative materials for the jacket 104a may include low-density polyethylene.

[043] Figs. 5a and 5b show exemplary embodiments of the relationship between different components of a stent delivery device 101, including the stent 102, outer assembly 105, and inner assembly 104. As shown in these figures, an outer assembly 105, including a clear outer portion 105a, a transition region 105b, and a opaque braided region 105c, surrounds an inner assembly 104, including multiple Pellethane jackets 104a along an interior tube 104b. A holding sleeve 104c assists in holding and identifying the proximal end of a stent 102. At the distal end of the stent 102 is a marker band 131 that marks the front edge of the stent 102, thereby assisting in proper stent position during deployment. The marker band 131 may be radiopaque to be visible under fluroscopy. The lead point 117 is positioned distal to the marker band 131. The braid 139 in the outer assembly 105 may extend across the opaque region 105c and the

LAW OFFICES

FINNEGAN, HENDERSON,  
FARABOW, GARRETT,  
& DUNNER, L.L.P.  
1300 I STREET, N. W.  
WASHINGTON, DC 20005  
202-408-4000



distal end. The lower durometer material is more flexible than higher durometer material. Thus, the delivery system 101 will gain in flexibility towards its distal end, where the stent delivery device may require a greater degree of precision in winding through tortuous anatomy. However, the structural integrity of the overall stent delivery device 100 will be maintained because a higher durometer material is used throughout a significant length of the inner assembly 104.

[045] Other embodiments of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. For example, the sequential increase in the durometer measure of subsequent contact areas of Figs. 6a-6c may occur at every other contact area, or other such trend, as long as there is an increase in flexibility from a proximal region to a distal region of the inner assembly 104. Also, there may be more than one distinct jacket layer 104a of Pellethane used in the illustrated embodiment depicted in Figs. 4a-4c, or stated differently, each of the jacket layers 104a1, 104a2, and 104a3 in Figs. 6a-6c may be Pellethane. More than or less than three jacket layers are possible in the illustrated embodiment depicted in Figs. 6a-6c. Furthermore, the length of the clear region 105a may be changed to suit the preference of health care workers so that either more or less of the constrained length of the stent 102 may be visible during deployment/reconstrainment. It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit of the invention being indicated by the following claims.

LAW OFFICES

FINNEGAN, HENDERSON,  
FARABOW, GARRETT,  
& DUNNER, L.L.P.  
1300 I STREET, N. W.  
WASHINGTON, DC 20005  
202-408-4000